

Product Name:T955 GPS Personal Tracker

Features:

Light, Fashionable, User friendly

- Compact size (65x43x19mm), Streamline, Light weight(60g), User friendly.
- Built-in G-Sensor, automatic Power saving mode entered when standing still, longer stand-by time.
- Removable battery, with optional High capacity battery
- Hands free call, Volume adjustable
- Vibrating alerts/ Ringtone alerts

User friendly Interface

- Geo Fence function, Multiple ways of setting: Mobile Phone/PC/Call centre
- Regular report function
- Real time setting your T955 through SMS/DTMF from authorized user

SMS/MMS, Clear, Convenient and Efficient.

- SMS report: The position of T955 send through SMS with nearby POI as reference point(Map Required).
- MMS report: The position of T955 send through MMS with a map of the location.(Map Required).

Voice report/monitor/Voice Communication(with authorized Number)

- Emergency call. In an emergency, 3 pre-set No. can be dialed, and send SMS message.
- 3 hot keys indicate 3 authorized number
- 20 pre-set authorized numbers, keep your cared one away from strangers
- Monitor function, hear it.

Mini-USB slot: System configuration/Charging/Data transferring.

- PC software, Easy to Manage.



Technical Performance

GPS Technical Performance

- NEMA0813 V3.01 potocal message
- Tracking -161dBm / Acquisition -141dBm
- Hot star < 1s
- Warm star < 32s
- Cold star < 34s
- Support AGPS function.

GSM/GPRS Technical Performance

- GSM Chipset: MTK6225
- GPRS Multi-slot Class10
- Tri-band GSM 900/1800/1900
Or GSM 850/1800/1900
- FTA Setting (Setting GPRS/WAP/SMS centre over the air)

Connected to PC

- T955 System setting
- Geo fence setting
- Authorized user setting
- Track Management



Specification

G-Sensor	Built-in 3-Axis G-Sensor (Recommend Bosch)
GPS Antenna	Ceramic Patch Active antenna 15x15x5mm
GPS Engine	M-Star P2 GPS engine board 13x16x3mm
GSM Antenna	Built-in Pi-Fa Antenna
GPS Power Consumption	Working<35~30mAh / Sleep <10uAh
Working time	Standby (GSM ON, GPS OFF): 72 hrs
	Full function(GSM ON, GPS ON): 12hrs
	Period report every 1/5/10/30 minutes (GSM ON, GPS OFF), 24hrs extend
Buttons	3 x Quick dial button
	1 x Power button



moving into free land

eBon Technologies Inc. | EBONTEK GROUP CORP.

12F.-7.,No.262, Xindian Rd., Xindian City Taipei County 23147, Taiwan R.O.C.

Tel : 886-2-89116562 ext.67

Fax : 886-2-89111224

www.ebontek.com

	1 x Volume+button
	1 x Volume- button
	1 x SOS button
Slots	1 x SIM Card slot
	1 x MicroSD Card slot
	1 x USB 10pin slot (Data transferring/Charging/System updates)
LED Indicator	1 x RED/GREEN Power Indicators
	1 x RED/GREEN GSM Indicators
	1 x RED/BLUE GPS Indicators
	1 x RED SOS Indicator
Speaker	built-in hi-fi speaker
Microphone	Built-in sensitive Microphone
Vibrate Alert	Yes
Battery	3.7V 650mAh Rechargeable Lithium battery (NOKIA Standard)
Operating Temperature Range	-20~+60°C
Dimensions	65x43x19mm
Weight	<60g
USB Port	USB1.1 slave HID device
Reserved Ports	20pin P=0.5mm FPC (connectable to external Earphone, Microphone, SPI I/F 3-wires, UART 4pins, 5xGPIO, Power+/-)
Accessories	Standard: Lithium battery
	110~240V AC / 5V DC 700mAh Power Travel Kit
	USB cable, Rope
	Optional:1300mAh Rechargeable Lithium battery , wristlet ; Water shield (magnetic, qualified with IPX 6)